

## Remote reading head, coding block, type 6727-32

- Low-wear identification system in accordance with the coding block method.
- In connection with MAK 3001, MAK 3002 as well as with other systems it guarantees a simple and reliable identification of supplier containers.
- Cordless data transmission
- For reading out coding block, type 6833.
- Highest reading reliability
- Standard rechargeable batteries



Technical data	
<b>Device-specific data</b>	
Sensor	Magneto-resistant
Transmission reliability	High redundancy with data transmission to reading station
Displays/control elements	2 LED/3 keys membrane keyboard
Resting position	Slot in the charging station
Number of readings	At least 1,000 (when battery is completely charged)
<b>Electrical data</b>	
Auxiliary energy	Exchangeable battery 4 x 1.2 V 850 mAh
Transmitter	FM, frequency 433.92 MHz, each radio reading system coded on the side of the transmitter and of the receiver, range of transmission 30 m
<b>Ambient conditions</b>	
Operating temperature	- 20 ... + 60 °C
Storage temperature	- 20 ... + 70 °C
Climatic classification	IUD in accordance with DIN 40040
Protective type	IP 65
<b>Mechanical data</b>	
Weight	0,36 kg
Casing	Plastic, ergonomic, impact-proof, waterproof
<b>Dimensions</b>	
<b>Ordering details</b>	
<b>Designation</b>	<b>Order no.</b>
Remote reading head, coding block, type 6727-32	221 751