



## MS2002+ Acceleration Sensor

The well proven technology of silicon micromachined capacitive sensors has been further improved by optimizing the sensor structure. Integration of electronics into an application specific IC results in a small high precision accelerometer which shows environmental and reliability performance similar to integrated circuits.

This accelerometer, built as triaxial device, suits ideally into seismic instrumentation. The DC coupled output in combination with the very low short- and long-term drift provides true engineering data that require no post-processing.

The micromachined capacitive accelerometer has become an attractive alternative against traditionally used FBA's. It's small dimensions, rugged construction and excellent reliability makes it especially suitable for unattended free-field instruments and instrumentation of structures, such as nuclear power plants, dams and seismic alerting systems. The sensors are factory calibrated and require no re-calibration. They are equipped with a fully comprehensive self-test function.

## Technical Specification MS2002+

### 1. Performance

#### ■ Principle

The acceleration sensing element is based on a micromechanical silicon chip, an ASIC for signal conditioning, and an EEPROM for storage of the calibration data. The micromechanical capacitive chip is manufactured using a 3-wafer silicon bulk-micromachining fusion bonding process. The signal conditioning IC translates the capacitance variation of the sensor chip into a calibrated output voltage. The gain, offset and nonlinearity corrections are programmed digitally during manufacturing.

■ Offset (at 0g)	2.5 V ± 200 µV/°C
■ Cross axis sensitivity	0.030 V/g
■ Hysteresis	none
■ Noise	typ. 10 µV/√Hz
■ Orientation	triaxial, horizontal (floor) mounting or vertical (wall) mounting
■ Non-Linearity	< 0.5 % of full scale
■ Frequency response	linear 0 to 150 Hz (accuracy ±1%)
■ Dynamic range (RMS)	> 84 dB (DC to 50 Hz)
■ Shock survival	6000 g (0.5 ms half sine)
■ Vibration survival	20 g RMS (random noise 20-500 Hz, 30 minutes)
■ Operating temperature	- 30 to 70°C

#### 1.1 MS2002+ triaxial Sensor (unipolar)

■ Measuring range	± 1 g
■ Sensitivity	2 V/g ± 400 ppm/°C
■ Supply voltage	+ 12 V (+10 % / -30 %)
■ Current consumption	typ. 6 mA @ 12 V
■ Output voltage	2.5 V ± 2 V

#### 1.2 MS2002+ triaxial Sensor (bipolar)

■ Measuring range	± 2 g / ± 10 g
■ Sensitivity	1 V/g (2 g sensor), 0.2 V/g (10 g sensor)
■ Supply voltage	± 5 V (± 5%)
■ Current consumption	typ. 6 mA @ 5V, 4 mA @ -5 V
■ Output voltage	0 V ± 2 V

### 2. Physical Characteristics

■ Housing	Aluminum, 80 x 80 x 60 mm (W x L x H)
■ Connector	Metallic self-latching push-pull connector with positioning key (LEMO)
■ Weight	0.5 kg
■ Protection degree	IP 67
■ Optional	mounted inside MR2002 recorder

Manufacturer:

**Syscom Instruments AG**

Imfeldstrasse 29

CH-8037 Zürich/Switzerland

A member of the BARTEC Group

Telefon +41 (1) 3 65 27 00

Fax +41 (1) 3 62 06 50

E-mail: info@syscom.ch

www.syscom.ch