

TC75X^{ex}-NI

Touch Computer Datasheet



Your workers in the field need a mobile computer to communicate with others and to access information. Only in this way they can work with maximum efficiency and improve service to customers.

The TC75X^{ex}-NI is the ultimate touch computer for your rugged environment and built to deliver the unstoppable performance you need. The TC75X^{ex}-NI is built for the toughest conditions and certified to the strictest Ex safety standards for use in Zone 2 and Class I, II, III Div 2. This professional grade device married the intuitive and elegant smartphone experience with today's most advanced enterprise-class features. Your workers get everything they need to work smarter and faster, able to deliver the kind of service that will put your business a step above the competition. You get a ultra-rugged device built to last for years with everything you need to streamline your workflows and maximize your return on investment. Access to practically all information in your back-end systems wherever and whenever you need it. The ability to collect more types of data quicker than ever before. Immediate Push-to-Talk communication with field staff, line managers, despatch coordinators and colleagues in the office. 4G LTE support for robust, wireless connections in the fastest mobile phone networks in the world. And an extensive range of accessories which meets the unique demands of practically all mobile employees. The TC 75X^{ex} series – a simple way of equipping your field team with a true mobile office – now also in a potentially explosive atmosphere.

Explosion protection

Marking ATEX	Ex II 3G Ex ic op is IIC T5 Gc Ex II 3D Ex ic op is IIIB T100 °C Dc IP 64
Certification	EPS 17 ATEX 1 028 X
Marking IECEx	Ex ic op is IIC T5 Gc Ex ic op is IIIB T100 °C Dc IP 64
Certification	IECEx EPS 17.0012X
Marking ETL	Class I Div. 2 Groups A, B, C and D Class II Div. 2 Groups F, G Class III; T4
Certification	5012876
	Other approvals and certificates, see bartec.com

User environment

Operating temperature	-20 °C to +50 °C (-4 °F to 122 °F)
Storage temperature (without battery)	-40 °C to +70 °C (-42 °F to 158 °F)
Relative humidity	5 % ~ 85 % (non-condensing)
Protection class (IEC 60529)	IP 64
Drop Specification	Multiple 2.4 m (94.5 inch) drop to concrete at room temperature MIL-STD-810G, Multiple 1.8 m (70.9 inch) drop to concrete across full operating temperature range
Tumble Specification	2,000 1 m (39.4 inch) tumbles; meets and exceeds IEC tumble specification

Technical Data

Processor	1.8 GHz hex core 64 bit processor
Memory (RAM)	4 GB RAM
Mass storage	32 GB Flash pSLC
Storage expansion	User accessible microSD - up to 32GB SDHC and up to 64 GB SDXC
SIM	2 Nano SIM, 1 SAM
Operating system	Android 8.1 (Oreo) with Mobility Extensions Security updates/patches on request
Size (L x W x H)	161 mm x 84 mm x 28 mm (6.3 inch x 3.3 inch x 1.1 inch)
Weight (with battery)	376 g (0.83 lb)
Display	4.7", bonded
Resolution	1280 x 720 pixels
Front glass	Corning Gorilla Glass
Touch function	Dual mode capacitive touch
Usability	With Stylus or bare or gloved fingertip input
Battery	Lithium polymer battery 3.7 V/4620 mAh (1S/2P) Battery change function Must only be changed and charged outside potentially explosive atmosphere.
Notifications	Audible tone; multi-color LEDs; vibration
Voice and audio	Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellulat circuit switch voice; HD Voice
Buttons	1 x on/off button 1 x function button 1 x scan button 2 x volume buttons (+/-) 4 x capacitive function buttons (home, menu, ESC, search function)

Barcode capture	SE4750-SR 1D/2D standard range imager Scan range at Code 39 barcode: 0.51 mm: 4.5 cm to 81.3 cm (0.02 inch: 0.18 inch to 32 inch) 0.08 mm: 7.9 cm to 14.2 cm (0.003 inch: 3.11 inch to 5.59 inch) supported symbologies/barcodes: see table
RFID Reader HF/NFC	Following RFID tags are supported: ISO 1443 type A and B; Felica- and ISO15693-card. P2P-mode and Card Emulation via UICC and Host
Radio Frequency Band	Worldwide LTE: 700,800/850/900/1800/2100/2600 (FDD 28,20,5,8,3,1,7) UMTS/HSPA/HSPA+: 850/900/1900/2100 GSM/GPRS/EDGE: 850/900/1800/1900 North-,Middle- and Southamerica LTE: 700/850/1900/AWS/2100, (FDD 13,12,17,5,26,225,4,1) UMTS/HSPA/HSPA+: 850,900,AWS,1900,2100 GSM/GPRS/EDGE: 850/900/1800/1900 CDMA: 850,1900(BCo,BC10,BC1)
WLAN-WiFi	2x2 MIMO; IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/w Data Rates 5 GHz: 802.11a/n/ac — up to 866.7 Mbps 2.4 GHz: 802.11b/g/n — up to 144 Mbps Operating Channels Chan 1 - 13 (2412 - 2472 MHz), Chan 36 - 165 (5180 - 5825 MHz), Chan 138, Chan 142 Channel Bandwidth 20, 40, 80 MHz Actual operating channels/ frequencies depend on regulatory rules and certification agency Security and Encryption WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP and AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC, EAP Fast2 and LEAP Features Wi-Fi Multimedia (WMM), Soft AP, MIMO with 2 Spatial Streams, 256 QAM Modulation on 5G GHz radio; Maximum Ratio Combining (MRC), Tx/Rx Low-Density Parity Check (LDPC), Transmit Beamforming(TxBF) and Beamformee (BFee) capability, Full IEEE 802.11 a/b/g/n legacy compatibility Certifications WFA (802.11n, 802.11ac, Mobile AP, Personal Hotspot, Miracast, WMM-PS, WMM-AC and Voice Enterprise) Fast Roam PMKID caching, Cisco CCKM, 802.11r, OKC
Bluetooth	v4.1 LE (low energy), Class 2, BT Wideband support HFPv1.6
GPS	Integrated Autonomous Assisted GPS (A-GPS), Navstar, GLONASS, Beidou
Camera	Backside: 13 MP with autofocus Frontside: fixed focus with 1.3 MP
Sensors	Light sensor: automatically adjusts display backlight brightness; Motion sensor: eCompass, 3-axis Gyro, 3-axis accelerometer
Externe I/O	only for use outside potentially explosive atmospheres USB 2.0 High Speed (Host and Client) 1 x Cradle Connector (OTG host, data exchange and charging) 1 x Port (PoGo Pin) for 2-slot charger

Software	No functional changes were made to the device due to the explosion protection. All tools and applications available from Zebra for the TC75X are compatible with the TC75X ^{ex} version. e.g. messaging via Workforce Connect PTT Express or the Mobility DNA solutions from ZEBRA
Mobility DNA	Mobility DNA solutions help you get more value out of our mobile computers by adding functionality as well as simplifying deployment and management of our mobile devices. For more information on these Zebra-only features, please visit www.zebra.com/mobilitydna
Warranty	1 year
Service contracts	COMFORT and ALL-IN
Scope of delivery	Touch Computer TC75X ^{ex} -NI Battery Hand strap Quick Start Guide
Also required	(not included in the delivery) Base station or battery charging station for charging

Accessories

see datasheet: TC75X^{ex}-NI Accessories
It is absolutely necessary to use original accessories from BARTEC!

Supported Symbologies / Barcodes

1D/Linear Symbol/Codes	Code 11 Code 39 Code 93 Code 128 Codabar Coupon Code Chinese 2 of 5 Discrete 2 of 5 EAN-8 EAN-13 Interleaved 2 of 5 MSI UPCA UPCE UPC/EAN supplementals Trioptic 39 RSS-14 RSS Expanded RSS Limited Webcode
2D Stacked and 2D Matrix Symbol/Codes	Aztec Australian 4-state Canadian 4-state Composite AB Composite C PDF-417 Data Matrix Dutch Kix Japanese 4-state Macro PDF-417 (Macro) Micro PDF-417 Micro PDF-417 microQR Maxi Code QR Code TLC39 UK 4-state US Planet US Postnet USPS 4-state (US4CB)

Ordering information

TC75X ^{ex} -NI with 4G/LTE US	B7-A264-1E32/33211100
TC75X ^{ex} -NI with 4G/LTE LATAM + CANADA (without Brazil)	B7-A264-1G32/33211100
TC75X ^{ex} -NI with 4G/LTE EMEA/APAC	B7-A264-1F32/33211100