

## RFID-TAG MOBILE, type 6952-51

- Reliable identification
- Robust key ring design
- ISO 15693



### Application

The 6952-51 transponder can be identified quickly and securely via the W-AS TAG terminal for product discharge specific to certain vehicles, e.g. construction vehicles..

### Function

The W-AS terminal type 6952-14 generates a high-frequency alternating electromagnetic field which receives the RFID transponder antenna. This alternating field activates the microchip in the transponder and the reader can read the data previously stored.

### Merkmale

- ISO Small robust housing
- ISO 15693 protocol
- 13.56 MHz high-frequency transponder
- Key ring 15693- Protokoll

Technical Data	
<b>Specific data</b>	
Frequency	13,56 MHz
Protocol	ISO 15693
Reading distance	Directly coupling
Data preservation EEPROM	min. 10 years (25°C)
Programm cycles EEPROM	100000
Size EEPROM	2 kByte
<b>Ambient conditions</b>	
Operation temperature	-25°C...+50°C
Store temperature	-25°C...+50°C
Protective system	IP 67
<b>Mechanical Data</b>	
Dimensions	See graph
Weight	ca. 11g
Material	Polyacetal (black)

**Dimensions**



**Data for purchase order**

Designation	Order Number
RFID-TAG MOBILE, type 6952-51	398470